



Product Data Sheet

# Supatone™ Ceiling Tiles

Gyprock Supatone Ceiling Tiles are bright white, economical plasterboard tiles that provide acoustic separation in commercial applications.

## Product Overview

Supatone Ceiling Tiles are squared edged, 10mm thick and available as 1200mm x 600mm tiles to suit common exposed grid systems. The tiles feature a poly-coated paper face. With Gyprock Supaceil in their core, they are sag resistant to provide longevity.

## Typical Applications

Supatone Ceiling Tiles are designed to suit standard suspended grid systems, typically in commercial construction. Suitable for a range of commercial environments, Supatone Ceiling Tiles are often used in shopping centres, offices, restaurants, factories and warehouses.



### Australian Made and Owned

Licensed by Australian Made Campaign Ltd



### Bright White

High reflectance in interior applications



### Ceiling Tile

Suitable for suspended grid systems



### 25 Year Warranty

Specify and install with confidence

## Technical Specifications

### Product Options

Supatone Ceiling Tiles are available in the following size:

Thickness	10mm
Width	600mm
Length	1200mm

Stockholdings may vary. For product availability and to place an order, contact your **nearest supplier**.

### Product Manufacture

Supatone Ceiling Tiles are manufactured for CSR Gyprock in Australia to stringent product specifications.

### Product Handling

**Transportation and manual handling:** Refer to the **Gypsum Board Manufacturers of Australia (GBMA) website** for recommended OH&S practices.

**Storage:** Protect from weather and moisture. Avoid products sagging by storing horizontally, supported on a level platform or full-width support members spaced at max. 600mm centres.

### Health and Safety

**Safety Data Sheets** are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

### Physical Properties

Nominal Weight*	7.2kg/m <sup>2</sup>
Fire Hazard assessed to AS/NZS3837 cone calorimeter test	Average Specific Extinction Area (ASEA) < 250 m <sup>2</sup> /kg Group Number 1 Report Reference WFRA 45759
Combustibility	In accordance with BCA Clause C1.12, Gyprock Supatone may be used wherever a non-combustible material is required by the Code.

\*Subject to reasonable manufacturing variance.

## Installation Instructions

### Resources

Gyprock makes available **resources** that provide comprehensive selection, design, installation and maintenance guidance.



#### Australian Made and Owned

Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



#### Manufactured for Life

Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.